

Hydraulic Load Cells are constructed from stainless steel. The load is distributed equally over the loading area of the cell by a thick, machined steel distribution plate. The load, when applied to the cell, causes a pressure increase in the hydraulic fluid, and this change in pressure may be measured via a Bourdon Tube Gauge or a variety of electrical transducers.

Two designs are available. An annular cell, and a solid cell for the measurement of compressive force. Both designs are available with the following readout methods:

1. A Bourdon Tube Gauge. This is the most simple method, but if directly connected requires access or visibility. The gauge can be mounted a short distance away and connected to the cell by a flexible hose.
2. Various types of electrical transducers, allowing for remote readout and data acquisition, are also available.



**FEATURES**

Simple, reliable, hydraulic operation	Low profile
Automated data acquisition systems are available	Remote readout capability

**FUNCTIONS**

Rock anchors	Soil anchors
Concrete pre and post-tensioning	Measurement of compressive loads between structural members

**TECHNICAL DATA**

Annular cells are available to suit all load ranges for both cable bolts and continuously threaded rock bolts. Please inquire.

Custom cells, either solid or annular can be fabricated to suit any specialized application or ranges.

A very stiff distribution plate is required, in order to insure that the load is applied equally over the pad of the cell. The outside diameter of this plate is equal to the loading area of the cell, with an identical inside diameter.

Bearing plates may not be required if adequate provision has been incorporated into the installation design. If required, the bearing plate is greater in diameter than the cell. Both bearing and distribution plates are machined from mild steel and zinc plated for corrosion protection.

Hydraulic Load Cells are sensitive to temperature changes, and we therefore do not recommend their use in applications where temperature fluctuations may occur.

For highest accuracy and temperature compensation, we recommend either strain gauge or vibrating wire type cells.

**ANCILLARY EQUIPMENT** (Specify when ordering)

Distribution plates	Data acquisition systems
Bearing plates	Digital electronic readout instruments

Optional fully enclosed, lockable housing to protect the data gauge

**SAMPLE PART NUMBER** (Specify O.D. and height when ordering)

eg: HLC-100-1  
 HLC: Hydraulic Load Cell  
 100: max. capacity required (Kips)  
 1: hole size in inches



Specifications may change without notice. LPB0003D



**RST Instruments Ltd.**  
 200 - 2050 Hartley Ave., Coquitlam, BC Canada V3K 6W5  
 Telephone: +1-604-540-1100 • Facsimile: +1-604-540-1005  
 Toll Free (USA & Canada): 1-800-665-5599  
 Email: info@rstinstruments.com  
[www.rstinstruments.com](http://www.rstinstruments.com)

The RST Instruments Management System is certified to ISO 9001:2000

